



**GASTROPARTS**

# Bakers Pride

- [EN]** Equipment
- [DE]** Geräte
- [ES]** Aparatos
- [FR]** Équipement
- [IT]** Attrezzature
- [PL]** Urządzenia
- [RU]** Оборудование

✉ [gastroparts@gastroparts.com](mailto:gastroparts@gastroparts.com)

☎ +48 56 657 00 66

📘 [fb.com/gastroparts.global](https://fb.com/gastroparts.global)

**GASTROPARTS.COM**





## thermostats

### control and safety thermostats

EGO

control thermostats

55.34\_ series



<b>Part No.</b>	376089	<b>Ref. No.</b>	M1098X
<b>description</b>	thermostat t.max. 370°C temperature range 140-360°C 3-pole probe ø 3.1mm probe L 263mm capillary pipe 1700mm shaft ø 6x4.6mm shaft L 23mm rotation 270°		

CAEM

control thermostats



<b>Part No.</b>	390790	<b>Ref. No.</b>	182500044
<b>description</b>	thermostat t.max. 300°C temperature range 50-280°C 1-pole 1NO 16A probe ø 3mm probe L 160mm capillary pipe 1450mm capillary pipe isolated 650mm gland nut shaft ø 6x4.6mm shaft L 22mm rotation 270° 250V		

INVENSYS / ROBERTSHAW

control thermostats



<b>Part No.</b>	376030	<b>Ref. No.</b>	M1032X
<b>description</b>	thermostat t.max. 288°C temperature range 38-288°C 2-pole 2NO 30A probe ø 5mm probe L 295mm capillary pipe 1540mm capillary pipe isolatedmm gland nut shaft ø 6x4.6mm shaft L 20mm shaft position upper 100-550°F		

<b>Part No.</b>	376031	<b>Ref. No.</b>	M1031X
<b>description</b>	thermostat t.max. 371°C temperature range 148-371°C 2-pole 2NO 30A probe ø 5mm probe L 285mm capillary pipe 1540mm capillary pipe isolatedmm gland nut shaft ø 6x4.6mm shaft L 20mm shaft position upper probe material zinc-plated 300-700°F		

## switches and momentary switches

### rocker/momentary rocker switches

30x22mm



<b>Part No.</b>	347662	<b>Ref. No.</b>	167600000
<b>description</b>	momentary rocker switch mounting measurements 30x22mm black 2CO 250V 16A steam connection male faston 6.3mm ambient temperature max. 100/55°C protection IP40		

### microswitches

pin-plunger actuated

M10



<b>Part No.</b>	345032	<b>Ref. No.</b>	151600020
<b>description</b>	microswitch with plunger thread M10x1 thread L 12mm 250V 16A 1CO connection male faston 6.3mm stroke 7mm mounting distance 22mm L 28mm ambient temperature max. 125°C type SP9603 actuating force: 180g		



## solenoid valves

### solenoid valves (water)

RPE

solenoid valves with reducers

single



1

<b>Part No.</b>	370692	<b>Ref. No.</b>	120800009
<b>description</b>	solenoid valve single straight 220-240VAC inlet 3/4" outlet 11.5mm input 10-12l/min output 0.32-0.42l/min t.max. 60°C duty cycle 100% RPE plastic flow regulating valve outlet green flow regulating valve inlet white 2-ways medium temp max. 25°C		

## fans

### hot air motors



1

<b>Part No.</b>	601799	<b>Ref. No.</b>	391500007 391500015
<b>description</b>	fan wheel D1 ø 197mm H1 43mm blades 45 D2 ø 8mm D3 ø 8mm H2 25mm		

## ignition parts

### pilot burners

ROBERTSHAW

pilot burners

11EA series



1

<b>Part No.</b>	107411	<b>Ref. No.</b>	M1054X M1055X
<b>description</b>	pilot burner ROBERTSHAW type 11EA 1 flame LPG code 10 for pipe ø 3/16" - 1/4" CCT		



1

<b>Part No.</b>	107412	<b>Ref. No.</b>	M1062X
<b>description</b>	pilot burner ROBERTSHAW type 11EA 1 flame natural gas for pipe ø 3/16" - 1/4" CCT		

## thermocouples

### thermocouple sets universal



1

<b>Part No.</b>	102283	<b>Ref. No.</b>	M1296A M1296X
<b>description</b>	thermocouple set ROBERTSHAW 5-piece L 72" - 1825mm		

## equipment-specific units

### for pizza ovens

#### firebricks



1

<b>Part No.</b>	850125	<b>Ref. No.</b>	T1192X
<b>description</b>	firebrick L 640mm W 528mm H 27mm		

**GASTRO**PARTS.COM

